

InstaCote™ ARA-10

Asphalt Repair Additive

InstaCote ARA-10 is a two-part polyurethane “Green Product” designed as an additive for asphaltic pothole cold patch material used by Municipalities to extend the life of typical cold patch material repairs. The additive when added to asphalt requires no special surface preparation and can be driven on immediately after blended asphalt is placed into the pothole.

Typical Physical Properties

Liquid	
Odor	Slight musty
Ph	N/A
VOC	0.0 lbs/gal
Appearance	Dark Amber
Weight	8 Lbs.
Viscosity	300 cP
NCO content	30.8%
Cure times	
Initial Cure	30 minutes
Full cure	3 hours at 0°F to 40°F 1 to 2 hours at above 40°F
Shelf life	Indefinite Resin, 6 months Isocyanate
Clean up solvent	Xylene, MEK, Isopropyl alcohol, Methyl Pryolidone
Solid	
Shrinkage	Negligible
Coverage est.	Vary based on 4% additive by weight blend
Flash Point	428°F
Recommended storage temperature	+ 60°F

PATENT PENDING



InstaCote™, Inc.
160 C. Lavoy Rd.
Erie, Michigan, USA 48133
Phone (734) 847-5260 Fax (734) 847-9008
Email: tom.nachtman@instacote.com