

InstaCote, Inc. TECHNICAL DATA

Contamination Control Fixative

CC Fix

Description: CC Fix is a high solids, latex based product designed for application to surfaces contaminated with beryllium, asbestos, radiological nucleotides (plutonium, uranium) or any other toxic or problematic particulate. CC Fix encapsulates and fixes contaminants to any surface and will not allow the treated contaminant to become airborne. CC Fix is applied as a liquid, cures to a hard, rugged coating and is resistant to peeling, chipping or spalling. CC Fix is non-toxic, non-hazardous, non-flammable and will not support biological growth.

Application: CC Fix is typically applied over CC Wet. CC Fix can be brushed, rolled, misted or spray applied. Spray application can best be accomplished with a hand pump, metal canister spray unit with fan tip. Fan tip will produce a mist pattern 1'-3' wide, and one gallon CC Fix will cover 320 ft².

Physical Properties:

State:	Liquid	Color:	Blue
Odor:	Latex	VOC:	>0.001 #/gal
Boiling Point:	214°F	Freezing Point:	28°F
Sp. Gr.:	1.10	Wt/gal:	9.1 lbs/gal
PH:	7.3	Viscosity:	250 cP @ 20°C
Vapor Pressure:	1.4 mmHg @ 25°C	Vapor Density:	0.6mg/cm @ 20°C
NFPA Ratings:	Hazard: 0	Health: 0	Fire: 0 Reactivity: 0