Section I – General Information:

Item Name: CC Epoxy 609, Part B Curing Agent

Manufactured by: InstaCote, Inc. 160 C Lavoy Road Erie, MI 48133 Phone (734) 847-5260 Fax (734) 847-9008 Emergency Phone (800) 359-2783

| Date MSDS Prepared: | June 6, 2001 | |
|--|---|--|
| Last Reviewed Date: | June 6, 2001 | |
| MSDS Preparer's Name: | Charles J. Smith, Chemist/M.S. | |
| Product Description: | Epoxy Encapsulation Media, Curing Agent | |
| Multiple Parts (Yes/No): | Yes | |
| Description of Related Comp: Acrylate Monomer Part A | | |

Section II – Ingredient/Identity Information:

This document is prepared pursuant to OSHA Hazard Communication Standard (29CFR 1910.1200). Where a proprietary ingredient is shown, the identity may be available as provided in this standard. This product is considered non-hazardous under OSHA Hazard Communication Standard (29CFR 1910.1200).

All components of this product are included in the EPA Toxic Substance Control Act (TSCA) Chemical Substance Inventory.

| Ingredient | CAS No. | TLV | STEL PEL | Content |
|----------------------|---------|------|----------|---------|
| | | | | |
| Triethylenetetramine | None | None | None | 100% |

Section III - Hazards Identification:

HMIS Hazard Rating – 3 (serious)

PRIMARY ROUTE OF ENTRY: Skin Absorption, Inhalation. Ingestion

- Inhalation: Inhalation of vapors causes irritation of the respiratory tract and may cause adverse systemic effects.
- Eye Contact: Contact of undiluted product will cause immediate severe irritation, pain and result in burns, necrosis and possible permanent damage. Repeated exposure may cause allergic reaction/ sensitization.
- Skin Contact: Prolonged and repeated contact may cause irritation and redness. Skin sensitization or allergic reaction may occur in some individuals. Not likely to be absorbed in sufficient quantity to increase overall toxicity.
- Ingestion: Low order of Toxicity

Chronic Effects of Overexposure: Low order of Toxicity. Product does not contain carcinogenic materials as defined by OSHA Hazardous Communications Act 1910.1200. Product, nor individual ingredients are not known mutagenic, teratogenic, or reproductive health hazards.

Section IV - First Aid Measures:

- Inhalation:Remove individual to fresh air. If difficulty with breathing,
administer oxygen. If unconscious, utilize artificial respiration.
Prevent aspiration of vomit. Turn victim's head to the side.
Assure mucous does not obstruct airway. Get emergency medial
assistance.
 - Eye Contact Flush with large volumes of tepid water. Irrigate under upper and lower lids. Seek medical assistance.
 - Skin Contact Wash with soap and water. Change soiled clothing immediately and laundry prior to re-use.
 - Ingestion: Do NOT induce vomiting; give large quantity of water, get immediate medical assistance. Never give anything by mouth to an unconscious person. If vomiting occurs, turn victim's head to the side. Assure mucous does not obstruct airway

Section V – Fire Fighting Methods:

HMIS Rating – 1 (Slight) Flash Point: 149°C (>300°F) Method: SETA Flash Auto-Ignition Temp.: Not Available Limits of Flammability: LEL: NA UEL: NA Extinguishing Media: CO₂, Alcohol Foam, dry chemical, water fog Special Fire Fighting Hazards: Self contained respirator equipment and Full protective clothing required when smoke or fumes are generated.

Section VI – Accidental Release Measures:

- Spills/Leaks: Ventilate area and eliminate all sources of ignition. Wear Appropriate protective rear, contain spill, salvage, clean up residue with absorbent material. Wash area with water and diluted acetic acid.
- Disposal Method: Dispose in accordance with federal, state and /or local Regulations. Landfill if solid, incinerate at agency approved Waste-disposal facility.

Section VII – Handling and Storage:

Shelf Life: One half calendar year (6 months) from date of receipt. Storage: Store in a cool, dry environment. Store indoors and in a secure manner.

Section VII – Exposure Controls/Personal Protection:

- Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build-up of heavy vapors.
- Personal Protection Equipment: DO NOT WEAR CONTACT LENSES when working with this product. Wear chemical goggles/safety glasses with side shields and rubber/latex gloves. Selection of items such as boots and apron will depend on the experience of the operator. Respirators are not required with the use of this product alone. Refer to the MSDS of the related component for this product. Wear respirator protection whenever a mist is generated such as spray application. Spray application in confined spaces, closed rooms, or tanks are areas where mist generation will exceed TLV or TWA. Refer to OSHA CFR29 1910.134 for recommended respiratory protection.

Section IX – Physical and Chemical Properties:

| Boiling Pt. (°C): | >N/Av | Water Solubility: | < 0.01% | | |
|----------------------------|---------------|--------------------------|---------|--|--|
| Percent VOC: | Nil | Specific Gravity: | 0.98 | | |
| Freeze Pt. (°C): | N/Av | pH: | N/A | | |
| Vapor Pressure (37°C) N/Av | | | | | |
| Vapor Density | > Air | Evaporation Rate | N/Av | | |
| Appearance: | Crystal Clear | liquid with slight straw | v color | | |

N/A, Not Applicable

N/Av, Not Available

Section X – Stability and Reactivity:

HMIS Rating – 0 (Minimal)
 Stability: Stabile
 Incompatibility: Strong acids, strong oxidizing agents
 Decomposition Products: Oxides of carbon and nitrogen, nitriles and amides from incomplete combustion and smoke.
 Hazardous Polymerization: Will not occur if handled per instructions.

Section XI – Toxicity Information:

HMIS Rating – 2 (Moderate)
PRIMARY ROUTE OF ENTRY: Dermal (Skin Absorption)
Inhalation: Inhalation of vapors causes irritation of the respiratory tract and may cause adverse systemic effects.
Skin Contact: Prolonged and repeated contact may cause irritation and redness. Skin sensitization or allergic reaction may occur in some individuals. Not likely to be absorbed in sufficient quantity to increase overall toxicity.
Chronic Effects of Overexposure: Low order of Toxicity. Product does not contain carcinogenic materials as defined by OSHA Hazardous Communications Act 1910.1200. Product, nor individual

ingredients are not known mutagenic, teratogenic, or reproductive health hazards.

Section XII – Ecological Information:

Marine Pollutant: Not Determined

Section XIII – Disposal Considerations:

Handle disposal of waste materials in a manner, which complies with federal, state and/or local regulations. Landfill if solid, incinerate at an agency approved waste-disposal facility.

Section XIV – Transportation Information:

National Motor Freight Classification (NMFC): 33880 Sub: 2 Class: 55 Description: Regulated-Use DOT Proper Shipping Name Emergency Response Guide Page No.: 60 DOT Reportable Quantity: Not Regulated DOT: Shipping Name: Triethylenetriamine, UN 2259, Class 8, Package group II Label: Corrosive Sub-Label: None International: Shipping Name: Triethylenetriamine, UN 2259, TDGCD 8, Package group II Label: Corrosive Sub-Label: None

Section XV – Regulatory Information:

| SARA, Title III Section 302: Not | a reportable substance | |
|---|------------------------|-----------|
| SARA, Title III Sections 311/312 | : Health Hazard: | Immediate |
| | Physical Hazard: | None |
| SARA, Title III Section 313: Not a reportable Substance | | |
| WHMIS Classification: Class | ss D, Div. 2, Sub B | |

Section XV – Other Information:

The information herein has been compiled from sources believed to be reliable and accurate at the time of review to the best of our knowledge. InstaCote, Inc. can not give any guarantees regarding information from other sources, and expressly does not make any warranties nor assumes any liability, in its use.

Complete.

MATERIAL SAFETY DATA SHEET Trade Name: CC Epoxy 609, Part A Resin

Section I – General Information:

Item Name: CC Epoxy 609, Part A Resin

Manufactured by: InstaCote, Inc. 160 C Lavoy Road Erie, MI 48133 Phone (734) 847-5260 Fax (734) 847-9008 Emergency Phone (800) 359-2783

| Date MSDS Prepared: | June 6, 2001 | |
|--|---|--|
| Last Reviewed Date: | June 6, 2001 | |
| MSDS Preparer's Name: | Charles J. Smith, Chemist/M.S. | |
| Product Description: | Epoxy Encapsulation Media, Acrylate Monomer | |
| Multiple Parts (Yes/No): | Yes | |
| Description of Related Comp: Aliphatic Amine Part B Curing Agent | | |

Section II - Ingredient/Identity Information:

This document is prepared pursuant to OSHA Hazard Communication Standard (29CFR 1910.1200). Where a proprietary ingredient is shown, the identity may be available as provided in this standard. This product is considered non-hazardous under OSHA Hazard Communication Standard (29CFR 1910.1200).

All components of this product are included in the EPA Toxic Substance Control Act (TSCA) Chemical Substance Inventory.

| Ingredient | CAS No. | TLV | STEL | PEL | Content |
|------------------|------------|------|------|------|---------|
| - | | | | | |
| Epoxy Resin | 25068-38-6 | None | None | None | >50% |
| Acrylate Monomer | 13048-33-4 | None | None | None | >50% |

Section III - Hazards Identification:

 HMIS Hazard Rating – 1 (slight)

 PRIMARY ROUTE OF ENTRY:
 Dermal (Skin Absorption)

 Inhalation:
 Low volatility of material makes inhalation an unlikely source of entry. No known health information on vapor inhalation.

 Eye Contact:
 Contact can cause mild irritation.

 Skin Contact:
 Prolonged and repeated contact may cause irritation and redness. skin sensitization or allergic reaction may occur in some individuals.

 Ingestion:
 Low order of Toxicity

Chronic Effects of Overexposure: Low order of Toxicity. Product does not contain carcinogenic materials as defined by OSHA Hazardous Communications Act 1910.1200. Product, nor individual ingredients are not known mutagenic, teratogenic, or reproductive health hazards.

Section IV - First Aid Measures:

Eye Contact – Flush with large volumes of tepid water. If irritation persists, seek medical assistance.

Skin Contact – Wash with soap and water. Change soiled clothing immediately and laundry prior to re-use.

Section V – Fire Fighting Methods:

HMIS Rating – 1 (Slight)
Flash Point: >93°C (200°F) Pensky Martin C.C.
Auto-Ignition Temp.: Not Available
Limits of Flammability: LEL: NA UEL: NA
Extinguishing Media: CO₂, Alcohol Foam, dry chemical, water fog
Special Fire Fighting Hazards: Self contained respirator equipment and full protective clothing required when smoke or fumes are generated. Electrical grounding is not required.

Section VI - Accidental Release Measures:

Spills/Leaks: Ventilate area and eliminate all sources of ignition. Wear appropriate protective rear, contain spill, salvage, clean up residue with absorbent material.

Disposal Method: Dispose in accordance with federal, state and /or local regulations. Landfill if solid, incinerate at agency approved waste-disposal facility.

Section VII - Handling and Storage:

Shelf Life: One calendar year (12 months) from date of receipt. Storage: Store in a cool, dry environment. Store indoors and in a secure manner.

Section VII – Exposure Controls/Personal Protection:

Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build-up of heavy vapors.

Personal Protection Equipment: DO NOT WEAR CONTACT LENSES when working with this product. Wear chemical goggles/safety glasses with side shields and rubber/latex gloves. Selection of items such as boots and apron will depend on the experience of the operator. Respirators are not required with the use of this product alone. Refer to the MSDS of the related component for this product. Wear respirator protection whenever a mist is generated such as spray application. Spray application in confined spaces, closed rooms, or tanks are areas where mist generation will exceed TLV or TWA. Refer to OSHA CFR29 1910.134 for recommended respiratory protection.

Section IX – Physical and Chemical Properties:

| Boiling Pt. (°C): | >100 | Water Solubility: | < 0.01% | | |
|--|-------|-------------------------|---------|--|--|
| Percent VOC: | Nil | Specific Gravity: | 1.1 | | |
| Freeze Pt. (°C): | N/Av | pH: | N/A | | |
| Vapor Pressure (20°C) 20 mm Hg | | | | | |
| Vapor Density | > Air | Evaporation Rate | N/Av | | |
| Appearance: Crystal Clear liquid with slight straw color | | | w color | | |
| | | | | | |

Section X - Stability and Reactivity:

HMIS Rating – 0 (Minimal)

Stability: This product must be mixed and handled according to directions for safety. Excessive heat and fume generation can occur if improperly handled. Not sensitive to mechanical impact.

Incompatibility: Strong acids, strong bases, amines, and mercaptans may initiate hazardous polymerization.

Decomposition Products: Oxides of carbon and nitrogen, aldehydes and various hydrocarbons from incomplete combustion and smoke.

Hazardous Polymerization: Will not occur if handled per instructions.

Section XI - Toxicity Information:

| HMIS Rating | -2 (Moderate) | | |
|---------------|---|--------------------------------------|--|
| PRIMARY R | OUTE OF ENTRY: | Dermal (Skin Absorption) | |
| Inhalation: | Low volatility of material makes inhalation an unlikely source of | | |
| | entry. No known hea | lth information on vapor inhalation. | |
| Eye Contact: | Contact can cause mi | ld irritation. | |
| Skin Contact: | Prolonged and repeated contact may cause irritation and redness. | | |
| | skin sensitization or allergic reaction may occur in some | | |
| | individuals. | | |
| | LD(50) Dermal | CASRN 25068-38-6 20 gm/kg Rabbit | |
| | | 74398-71-3 2 gm/kg Rabbit | |
| Ingestion: | Low order of Toxicity | ý | |
| | LD(50) Oral | CASRN 25068- 38-6 11.4 gm/kg Rat | |
| | | 74398-71-3 5.0 gm/kg Rat | |
| | | | |

Chronic Effects of Overexposure: Low order of Toxicity. Product does not contain carcinogenic materials as defined by OSHA Hazardous Communications Act 1910.1200. Product, nor individual ingredients are not known mutagenic, teratogenic, or reproductive health hazards.

Section XII – Ecological Information:

Marine Pollutant: Not Determined

<u>Section XIII – Disposal Considerations</u>:

Handle disposal of waste materials in a manner, which complies with federal, state and/or local regulations. Landfill if solid, incinerate at an agency approved waste-disposal facility.

Section XIV – Transportation Information:

National Motor Freight Classification (NMFC): 156240 Sub: - Class: 55 Description: Resin Emergency Response Guide Page No.: Not Regulated DOT Reportable Quantity: Not Regulated DOT: Not Regulated International: Not Regulated

Section XV - Regulatory Information:

SARA, Title III Section 302: Not a reportable substance SARA, Title III Section 311/312: Health Hazard:

Immediate Delayed None

Physical Hazard: SARA, Title III Section 302: Not a reportable substance WHMIS Classification: Class D, Div. 2, Sub. Div. B

Section XV – Other Information:

The information herein has been compiled from sources believed to be reliable and accurate at the time of review to the best of our knowledge. InstaCote, Inc. cannot give any guarantees regarding information from other sources, and expressly does not make any warranties nor assumes any liability, in its use.

Complete